



Precise and uniform
water distribution

Sprinkler irrigation systems with quick connect couplings

- > **Easy installation and removal**
with quick-connect couplings
- > **Lightweight yet durable**
for frequent handling
and transportation
- > **Leak-tight seals**
under low pressures



Technical details

Pipe diameters (mm): 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 200

Pipe lengths (m): 5, 6, other lengths available on request

Nominal pipe pressure (PN): 4-6-8-10

Material: PE 100

Product features

UV resistant

Recyclable

10+ year lifespan

Usage

Number of seasons: multi-season

Topography: flat to slightly slopy

Soil types: all

Placement: surface

Application areas

- Row crops
- Field crops

Sprinkler details

Nozzle	Pressure (bar)	Flow rate (m ³ /h)	Irrigation diameter (m)
5.0 x 4.0	3.0	2.00	20
	4.0	2.20	24
5.0 x 2.3	3.0	1.60	20
	4.0	1.80	24
4.2 x 2.3	3.0	1.45	20
	4.0	1.60	24
3.8 x 2.3	3.0	1.35	20
	4.0	1.50	24
3.2 x 2.3	3.0	1.20	20
	4.0	1.30	24



Find the system that suits
your crops best from
our wide range of drip
irrigation technology

wienerberger Türkiye

Head Office: No: 403/1 Ankara Street, Yenişehir Mahallesi, Pendik, İstanbul, 34912

Niğde Factory: No: 8, 51200, 3rd Street, OSB Fertek Mahallesi, Niğde Organized Industrial Zone

İstanbul:(0216) 378 36 20 - Niğde:(0388) 502 00 15,

E pipelife@pipelife.com.tr F (0216) 378 36 27, www.pipelife.com.tr